

SAFETY DATA SHEET

This safety data sheet complies with the requirements of: 29CFR1910.1200

Issue Date 09-Dec-2024	Revision Date 09-Dec-2024	Version 1	
Product identifier Product Name	Seal Bond® 406		
Other means of identification Product Code UN/ID no. Synonyms	Seal Bond® 406		
<u>Recommended use of the chemica</u> Recommended Use Uses advised against	<mark>Il and restrictions on use</mark> Sealant. For exterior use only. Do not use indoors.		
Details of the supplier of the safety data sheet			
Manufacturer Address	Seal Bond 1251 E. Mt. Garfield Rd. Norton Shores, MI 49441 800-252-4144		
Emergency telephone number Emergency Telephone	Call CHEMTREC Day or Night: Within USA and Canada: 1-800 424-9300		
2. HAZARDS IDENTIFICATION			

Classification

OSHA Regulatory Status

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation Category 2	
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Aspiration toxicity	Category 1
Flammable liquids	Category 3

Label elements

Emergency Overview

Danger

Hazard statements Harmful if inhaled Causes skin irritation Causes serious eye irritation May cause genetic defects May cause cancer May be fatal if swallowed and enters airways Flammable liquid and vapor



Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Wash face, hands and any exposed skin thoroughly after handling

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention Specific treatment (see first aid information on this label) IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water If skin irritation occurs: Get medical advice/attention Take off contaminated clothing and wash before reuse IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

May be harmful in contact with skin
 Toxic to aquatic life with long lasting effects
 Harmful to aquatic life
 Unknown acute toxicity
 35% of the m

35% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

<u>Mixture</u> This product is a mixture. This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Common name	Sealant and Caulk.
Synonyms	SEALANT.
Chemical nature	Organic solvents and additives.

Chemical Name	CAS No.	Weight-%	Trade Secret
Hydrocarbon Resin	69430-35-9	30 - 40%	*
Styrene/Butadiene Copolymer	66070-58-4	20 - 30%	*

Aromatic Naptha (with <0.1% Benzene)	64742-95-6	20 - 30%	*
1,2,4 Trimethylbenzene	95-63-6	10 - 20%	*
Xylene	1330-20-7	0 - 10%	*
Cumene	98-82-8	0 - 10%	*

4. FIRST AID MEASURES

Description of first aid measures

General advice	Contains petroleum distillate. Harmful or fatal if swallowed.Vapor harmful. May affect the brain or central nervous system causing dizziness, headache, or nausea. Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.		
Eye contact	In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.		
Skin contact	Wash thoroughly with soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. In the case of skin irritation or allergic reactions see a physician.		
Inhalation	Move to fresh air in case of accidental inhalation of vapors. If continued difficulty with breathing is experienced, get medical attention immediately.		
Ingestion	Not an expected route of exposure. If swallowed, do not induce vomiting. Get medical attention immediately.		
Self-protection of the first aider	First aider: Pay attention to self-protection!.		
Most important symptoms and effects, both acute and delayed			
Symptoms	May cause skin irritation. May cause eye irritation.		
Indication of any immediate medical attention and special treatment needed			
Note to physicians	Treat symptomatically.		
5. FIRE-FIGHTING MEASURES			

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO2). Sand. Use foam or water FOG as a last resort.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Sealed container may rupture/burst when heated or exposed to excessive heat.

Hazardous combustion products Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.

Explosion dataSensitivity to Mechanical Impact Not sensitive.Sensitivity to Static DischargeMay be ignited by heat, sparks or flames.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures			
Personal precautions	No action should be taken involving any personal risk or without suitable training. Use personal protective equipment as required.		
Other Information	Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area).		
For emergency responders	Use personal protection recommended in Section 8.		
Environmental precautions			
Environmental precautions	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent product from entering sewers, drains, or waterways. Local authorities should be advised if significant spillages can not be contained. See Section 12 for additional ecological information.		
Methods and material for containm	ent and cleaning up		
Methods for containment	Contain spillage with non-combustible absorbent material, e.g. sand, earth, diatomaceous earth, vermiculite.		
Methods for cleaning up	Pick up the absorbed material (described just above) and transfer to properly labeled containers for disposal according to local / national regulations (see Section 13).		
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.		
	7. HANDLING AND STORAGE		
Precautions for safe handling			
Advice on safe handling	Use personal protective equipment as required. Remove all sources of ignition. Use only outdoors.		
Conditions for safe storage, including any incompatibilities			
Storage Conditions	Keep containers tightly closed in a cool, dry, well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition.		
Incompatible materials	Strong acids. Strong oxidizing agents.		

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
1,2,4 Trimethylbenzene 95-63-6	-	-	TWA: 25 ppm TWA: 125 mg/m ³
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	
Cumene 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m ³ (vacated) S* S*	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m ³

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

 Engineering Controls
 Use natural cross ventilation, local (mechanical) pick-up, and/or general area mechanical cross ventilation. Ventilation pattern should be designed to prevent accumulation of vapors. Ventilation must be sufficient to maintain vapor concentrations below the TWA limits outlined above.

 Individual protection measures, such as personal protective equipment

Eye/face protectionWear safety glasses with side shields (or goggles).Skin and body protectionWear protective gloves and protective clothing that is resistant to chemical penetration.Respiratory protectionNo protective equipment is needed under normal use conditions. If exposure limits are
exceeded or irritation is experienced, a NIOSH/MSHA approved respiratory protectionGeneral Hygiene ConsiderationsWash face, hands and any exposed skin thoroughly after handling. Wash contaminated
clothing before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Appearance	Paste/Gel Viscous	Odor	Solvent (Mineral Spirits)
Color	Clear	Odor threshold	Aromatic 1-30 PPM. Odor thresholds vary greatly. Do not rely on odor threshold alone to determine potentially hazardous substances.
Property pH	<u>Values</u> Not applicable	Remarks • Method	
Melting point/freezing point	None / -70 276F None / -94 °F	Melting Point is not appli shown.	cable. Freezing points are
Boiling point / boiling range Flash point Evaporation rate Flammability (solid, gas)	> 154 276F / 310 °F > 40.5 276F / > 105 °F 0.1 N/A	Setaflash Butly acetate = 1	
Flammability Limit in Air		Flammable above 105 de C.	egrees F and 40.5 degrees
Upper flammability limit: Lower flammability limit: Vapor pressure Vapor density Specific Gravity Water solubility Solubility in other solvents	7.0 1.6 0.3 (kPa) 5.3 0.95-1.05 Insoluble Soluble in aromatic and aliphatic	@ 20 °C Where: Air = 1 at 68 deg Water = 1g/ml	rees F (20 degrees C)
Partition coefficient Autoignition temperature Decomposition temperature Kinematic viscosity Dynamic viscosity Explosive properties Oxidizing properties	solvents. N/A 330 276F / 626 °F N/A N/A N/A Vapor accumulation could flash or exp None	No data available. blode if ignited.	

Other Information

Softening point
Molecular weight
VOC Content (%)
Density
Bulk density

Not applicable 330 g/l N/A 8.0 to 8.3 lb/gal Not applicable

10. STABILITY AND REACTIVITY

Reactivity Not applicable

Not applicable

Chemical stability

Stable.

Possibility of Hazardous Reactions None under normal use.

Hazardous polymerization Hazardous polymerization does not occur.

<u>Conditions to avoid</u> Avoid static discharge. Avoid heat, sparks, and open flame.

Incompatible materials Strong acids. Strong oxidizing agents.

Hazardous Decomposition Products

Combustion may produce carbon monoxide, carbon dioxide, and other asphyxiants.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	Toxicological testing has not been conducted for this product overall. Available toxicological data for individualingredients are summarized below.
Inhalation	Avoid breathing vapors or mists.
Eye contact	Avoid contact with eyes. Contact with eyes may cause irritation.
Skin contact	May cause irritation.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately. Not an expected route of exposure.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Aromatic Naptha (with <0.1% Benzene) 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat)4 h
1,2,4 Trimethylbenzene 95-63-6	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m³ (Rat)4 h
Xylene 1330-20-7	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit) > 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat)4 h = 5000 ppm (Rat)4 h
Cumene 98-82-8	= 1400 mg/kg (Rat)	= 12300 µL/kg (Rabbit)	= 39000 mg/m ³ (Rat)4 h > 3577 ppm (Rat)6 h

Information on toxicological effects

Symptoms

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chamical Nama			NTD	06114
	any ingredie	nt as a carcinogen.		
Carcinogenicity	The table be	low indicates whether each	agency (ACGIH, IARC, N	ITP, or OSHA) has listed
Germ cell mutagenicity	•	does not contain any ingre	5	5 ,
Sensitization	5	sensitization of susceptible		
Corrosivity	Not classifie			
Serious eye damage/eye Irritation	Irritating to e	yes, respiratory system and	d skin.	
Skin corrosion/irritation		kin irritation.		

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylene	-	Group 3	-	-
1330-20-7				
Cumene	-	Group 2B	Reasonably Anticipated	Х
98-82-8				

Legend

IARC (International Agency for Research on Cancer) Group 1 - Carcinogenic to Humans Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans Group 3 - Not classifiable as a human carcinogen.

Reproductive toxicity None known for product as a whole. **Developmental Toxicity** None known for product as a whole. Teratogenicity None known. STOT - single exposure N/A. STOT - repeated exposure N/A. Aspiration hazard N/A.

Numerical measures of toxicity - No information available

The following values are calculated based on chapter 3.1 of the GHS document For exterior use only. Do not use indoors.

ATEmix (oral)	5,296.00
ATEmix (dermal)	2,383.00
ATEmix (inhalation-dust/mist)	1.57

12. ECOLOGICAL INFORMATION

Ecotoxicity

14.75% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Aromatic Naptha (with <0.1% Benzene) 64742-95-6	-	9.22: 96 h Oncorhynchus mykiss mg/L LC50	6.14: 48 h Daphnia magna mg/L EC50
1,2,4 Trimethylbenzene 95-63-6	-	7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through	6.14: 48 h Daphnia magna mg/L EC50
Xylene 1330-20-7		 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 13.4: 96 h Pimephales promelas mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 780: 96 h Cyprinus carpio mg/L 	0.6: 48 h Gammarus lacustris mg/L LC50 3.82: 48 h water flea mg/L EC50

		LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50	
Cumene 98-82-8	2.6: 72 h Pseudokirchneriella subcapitata mg/L EC50	6.04 - 6.61: 96 h Pimephales promelas mg/L LC50 flow-through 2.7: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 4.8: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 5.1: 96 h Poecilia reticulata mg/L LC50 semi-static	7.9 - 14.1: 48 h Daphnia magna mg/L EC50 Static 0.6: 48 h Daphnia magna mg/L EC50

Persistence and degradability N/A.

IN/A.

Bioaccumulation

N/A.

Chemical Name	Partition coefficient
1,2,4 Trimethylbenzene 95-63-6	3.63
Xylene 1330-20-7	3.15
Cumene 98-82-8	3.7

Other adverse effects

N/A

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

Disposal should be in accordance with applicable local, regional, national and international laws and regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number U055 U239

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene 1330-20-7	-	Included in waste stream: F039	-	U239
Cumene 98-82-8	-	-	-	U055

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Xylene	Toxic
1330-20-7	Ignitable
Cumene	Toxic
98-82-8	Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID no.	UN 1263
Proper shipping name	Combustible liquid, n.o.s
Hazard Class	3
Packing Group	III
Special Provisions	NOT HAZARDOUS FOR TRANSPORTATION UNLESS PACKAGED IN CONTAINERS

	WITH A CAPACITY OF 118 GALLONS OR MORE
TDG	Not regulated.
MEX	Not regulated.
ICAO (air)	Not regulated.
<u>IATA</u> UN/ID no. Proper shipping name Hazard Class Packing Group ERG Code	UN 1263 PAINT RELATED MATERIAL 3 III 128
IMDG UN/ID no. Proper shipping name Hazard Class Packing Group EmS-No.	UN 1263 PAINT RELATED MATERIAL 3 III F-E
RID	Not regulated.
ADR	Not applicable in the United States. Not regulated.
ADN	Not applicable in the United States. Not regulated.
	15. REGULATORY INFORMATION

15. REGULATORY INFORMATION

International Inventories TSCA All o

All of the components of this product are listed on the US TSCA (Toxic Substances Control Act) Inventory or are exempt. All of the components of this product are listed on the DSL.

DSL/NDSL

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
1,2,4 Trimethylbenzene - 95-63-6	1.0
Xylene - 1330-20-7	1.0
Cumene - 98-82-8	1.0
SARA 311/312 Hazard Categories	
Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Quantities	Substances
Xylene 100 lb	Х
1330-20-7	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene	100 lb	-	RQ 100 lb final RQ
1330-20-7			RQ 45.4 kg final RQ
Cumene	5000 lb	-	RQ 5000 lb final RQ
98-82-8			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65				
Cumene - 98-82-8	Carcinogen				

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
1,2,4 Trimethylbenzene	X	Х	Х
95-63-6			
Xylene	X	Х	Х
1330-20-7			
Cumene	X	Х	Х
98-82-8			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability	2 Instability	0	Physical and Chemical Properties *
HMIS Chronic Hazard Star Lege	Health hazards 2	Flammability 2 Health Hazard	2 Physical	hazards 0	Personal protection -

Prepared By Issue Date Revision Date Revision Note N/A Prepared by Kelly Iverson 09-Dec-2024 09-Dec-2024

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.