

SAFETY DATA SHEET

Safety Data Sheet

Revision Date: August 23, 2023

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Sealant Product Name: SB 404 - Translucent

1.2. Intended Use of the Product

Sealant

1.3. Name, Address, and Telephone of the Responsible Party

Company

Seal Bond 1251 E. Mt. Garfield Rd. Norton Shores, MI 49456 (616) 850-0507 (ph) (616) 850-0530 (fx)

1.4. Emergency Telephone Number

Emergency Number: Chemtrec 800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

| GHS Classification: | Not a hazardous substance or mixture. |
|--|--|
| Acute Effects: Delayed Effects: Indication of Immediate Medical Attention and Special Treatment Needed, If Needed: | No information on significant adverse effects. No information on significant adverse effects. |
| | Treat symptomatically and supportively. |
| GHS Label Elements Symbol(s): Signal Word: Hazard Statement(s): | None. None. None known. |
| Precautionary Statement(s) Prevention: | Use only outdoors or in a well-ventilated area. Avoid release to the environment. |

SB 404 Translucent, 2023/08/23

| Response: | None known. |
|-----------|---|
| Storage: | Keep in properly labeled containers. Store in accordance with the particular national regulations. |
| Disposal: | Dispose of contents/container in accordance with local/regional/national/ international regulations. |

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Nature: Silicone elastomer

This product is a mixture

Contains no hazardous ingredients according to GHS

SECTION 4: FIRST AID MEASURES

General Advice:

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

| Inhalation: | IF INHALED: Remove to fresh air. |
|---------------|--|
| | Get medical attention if symptoms occur. |
| Skin Contact: | IF ON SKIN: Wash with soap and water as a precaution. |
| Eye Contact: | IF IN EYES: Flush eyes with water for several minutes, Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist. |
| Ingestion: | No emergency medical treatment necessary. |

Most Important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

SECTION 5: FIRE-FIGHTING MEASURES

| Suitable Extinguishing Media: | Use carbon dioxide, regular dry chemical, alcohol-resistant foam or water. |
|---------------------------------|--|
| Unsuitable Extinguishing Media: | None known. |

| Specific Hazards Arising from the Chemi | cal | | |
|--|--|--|--|
| Hazardous Combustion Products: | Carbon oxides and silicon oxides | | |
| Unusual Fire and Explosion Hazards: | Exposure to combustion products may be a hazard to health. | | |
| Special Protective Equipment and Precautions for Firefighters: | | | |
| Procedures: | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area. | | |
| | Special protective equipment: Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment. | | |

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures:

Follow safe handling advice and personal protective equipment recommendations.

Environment Precautions:

Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and Materials for Containment and Cleaning Up:

Wipe up or scrape up and contain for salvage or disposal. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, Sections 13 and 15 of this SDS provide information regarding certain local or national requirements. See sections: 7, 8, 11, 12 and 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice. Use only with adequate ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. **Conditions for safe storage:**

Keep in properly labelled containers. Store in accordance with the particular national regulations.

| Incompatible Materials: | Strong oxidizing agents |
|--------------------------------------|-------------------------|
| Unsuitable materials for containers: | None known |

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable. Although some of the components of this product may have exposure guidelines, no exposure would be expected under normal handling conditions due to the physical state of the material.

Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations. **Individual protection measures:**

| Eye/face Protection: | Use safety glasses (with side shields). |
|----------------------|--|
| Skin Protection | |
| Hand: | Chemical protective gloves should not be needed when handling this material. Consistent with general hygienic practice for any material, skin contact should be minimized. |
| Other: | No precautions other than clean body-covering clothing should be needed. |

Respiratory Protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions, no respiratory protection should be needed; however, if handling at elevated temperatures without sufficient ventilation, use an approved airpurifying respirator.

The following should be effective types of air-purifying respirators: Organic vapor cartridge.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

| Physical State: Liquid Appea | irance: | Paste | |
|-------------------------------|----------------------------------|--|-----------------------------------|
| Color: | Colorless | Physical Form: | : Paste |
| Odor: A | Acetic Acid Odor Threshol | d: Not available pH: Not applica | able Melting Point: Not available |
| Boiling Point: | Not applicable | Decomposition: | Not available |
| Flash Point: | >100 °C (closed cup) | Evaporation Rate: | Not applicable |
| | Not classified as a | | |
| OSHA Flammability Class: | | Vapor Pressure: | Not applicable |
| | flammability hazard | | |
| Vapor Density (air = 1): | Not available | Density: | 1.007 |
| Specific Gravity (water = 1): | Not available | Water Solubility: | Not available |
| Log KOW: | Not available | Coeff. Water/Oil Dist: | Not available |
| KOC: | Not available | Auto Ignition: | Not available |
| Viscosity: | Not applicable | VOC: | Not available |
| | | | Not available |
| Volatility: | Not available | Molecular Formula: | |
| | | | |

NOTE: The physical data presented above are typical values and should not be construed as a specification.

SECTION 10: STABILITY AND REACTIVITY

| Reactivity: Chemical Stability: Possibility of Hazardous Reactions: | Not classified as a reactivity hazard. Stable at normal temperatures and pressure. Use at elevated temperatures may form highly hazardous compounds. Can react with strong oxidizing agents. Acetic acid is formed upon contact with water or humid air. When heated to temperatures above 150 °C (300 °F) in the presence of air, trace quantities of formaldehyde may be released. See OSHA formaldehyde standard, 29 CFR 1910.1048 Hazardous decomposition products will be formed at elevated temperatures. |
|---|---|
| Conditions to Avoid: | None known. |
| Incompatible Materials: | Strong oxidizing materials |
| formaldehyde. | |

| SECTION 11: TOXICOLOGICAL INFORMATION | | | | | |
|---------------------------------------|---------|----------------------------|----------|--|--|
| Result | Species | Dose | Exposure | Remarks | |
| LD50 Oral | Rat | >5,000 mg/kg | N/A | Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts. | |
| LC50 Inhalation | N/A | Has not been determined | N/A | Brief exposure (minutes) is not likely to cause adverse effects. Vapor from heated material may cause respiratory irritation. | |

2023-08-23

SB 404 Translucent, 2023/08/23

| LD50 Dermal | Rabbit | >2,000 mg/kg | N/A | Prolonged skin contact is unlikely to result in absorption of harmful amounts. |
|--|---------------|---|---|--|
| Skin Corrosion/Irritation | n: | Prolonged exposure | e not likely to d | cause significant skin irritation. |
| Serious Eye Damage/Ey Sensitization: | e Irritation: | May cause slight te Corneal injury is unl May cause mild eye | ikely. | ritation. |
| Sensitization. | | Contains component | (s) which did n | not cause allergic skin sensitization in |
| | Skin | contains component | (S) WHICH UIU I | |
| | • | guinea pigs. | | |
| | Respiratory | No relevant information | ation found. | |
| Specific Target Organ Syst Toxicity (Single Exposure) | | aluation of available o xicant. | lata suggests t | hat this material is not an STOT-SE |
| Specific Target Organ Sy Toxicity (Repeated Expos | | For the major comp Based on available additional significant | e data, repeate | ed exposures are not anticipated to cause ts. |
| Carcinogenicity: | | product and are not conditions or foresee For this family of m studies which used re | expected to be able emergen aterials: Did no outes of expos sults have beer | ot cause cancer in long-term animal ure considered relevant to industrial n reported in other studies using routes |
| Teratogenicity: | | - | nt(s) which did | not cause birth defects or any other |
| Reproductive Toxicity: | | Contains component studies. | (s) which did n | not interfere with reproduction in animal |
| Mutagenicity: | | | | re negative in in vitro genetic toxicity ich were negative in animal genetic |
| Aspiration Hazard: | | Based on physical p | properties, not | likely to be an aspiration hazard. |

SECTION 12: ECOLOGICAL INFORMATION

| Toxicity | No data available |
|----------|-------------------|
| | |

Persistence and Degradability: Bioaccumulative Potential: No data available No data available No data available **Mobility in Soil:**

SECTION 13: DISPOSAL CONSIDERATIONS

Disposal Methods:

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Recycler. Reclaimer. Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section10 Regulatory Information, MSDS Section 15

Treatment and disposal methods of used packaging:

Dispose of unused product properly. Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14: TRANSPORT INFORMATION

DOT

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

Transport in bulk according to Annex I Not regulated for transport or II of MARPOL 73/78 and the IBC or Consult IMO regulations before transporting ocean bulk IGC Code

Classification for AIR transport (IATA/ICAO): Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

SECTION 15: REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Rightto-Know Act of 1986) Sections 311 and 312 No SARA Hazards

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Rightto-Know Act of 1986) Section 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103

| Name | CASRN | RQ (RCRA Code) | |
|------------------|----------|----------------|--|
| Acetic Acid | 64-19-7 | 5,000 lbs RQ | |
| Acetic Anhvdride | 108-24-7 | 5.000 lbs RQ | |

Pennsylvania Right To Know

The following chemicals are listed because of the additional requirements of Pennsylvania law:

Components:

| Name | CASRN | |
|---|------------|--|
| Polydimethylsiloxane hydroxy-terminated | 70131-67-8 | |
| Silicon dioxide | 7631-86-9 | |

Components:

California Prop. 65


This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SECTION 16: Other Information

Issue Date: 8/23/2023 NFPA Ratings:



Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe HMIS

III:

| HEALTH | 10 |
|-----------------|----|
| FLAMMABILITY | 11 |
| PHYSICAL HAZARD | 00 |

0 = Not Significant, 1 = Slight, 2 = Moderate, 3 = High, 4 = Extreme, * = Chronic

Key/Legend:

AICS (Australia); DSL (Canada); IECSC (China); REACH (European Union); ENCS (Japan); ISHL (Japan); KECI (Korea); NZIOC (New Zealand); PICCS (Philippines); TCSI (Taiwan); TSCA (USA); ACGIH – USA. ACGIH Threshold Limit Values (TLV); NIOSH REL – USA. NIOSH Recommended Exposure Limits; OSHA P0 – USA. OSHA – TABLE Z-1 Limits for Air Contaminants – 1910.1000; OSHA Z-1 – USA. Occupational Exposure Limits (OSHA) – Table Z-1 Limits for Air Contaminates; OSHA Z-3 – USA. Occupational Exposure Limits (OSHA) – Table Z-3 Mineral Dusts; ACGIH / TWA – 8-hour, time-weighted average; NIOSH REL / TWA – Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek; NIOSH REL / ST – STEL – 15-minute TWA exposure that should not be exceeded at any time during a workday; OSHA P0 / TWA - 8-hour, time-weighted average; OSHA Z-1 / TWA - 8-hour, time-weighted average; OSHA Z-3 / TWA - 8-hour, time-weighted average

Disclaimer:

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations.

Party Responsible for the Preparation of This Document

Seal Bond 1251 E. Mt. Garfield Rd. Norton Shores, MI 49444 (616)850-0507

08/23/2023

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.